

“Slurry Blast” Systems

from Wet Technologies, Inc.

Deburring
Descaling
Bonding preparation
Mold cleaning
Auto-Marine-Aircraft
overhaul

Standard machine features include:

- 100% closed-loop design
- Stainless Steel cabinet construction
- Pulse-free slurry delivery system
- Continuous abrasive concentration rating up to 40% by volume
- Pump-diverted slurry agitation
- Automatic slurry filtration
- Boron Carbide Blast Nozzle
- Large, mushroom-type, thigh-depression switches
- On-demand window wash
- External, hinged, light box
- 500 lb. capacity screened work table.
- Heavy-duty, replaceable, gummed rubber curtains on interior walls
- Critical feed and water lines inside the cabinet enclosure for maximum leak protection
- Quick-disconnect couplings for fast, easy, service
- Standard cabinet base sizes: 36”x36”, 50”x50”, 60”x60”



*Standard Manual Model WTV50”
with Closed Loop Filtration,
Vertical Door, Turntable*

Control package includes Blast Nozzle air pressure regulator/gauge, rinse water air pressure regulator/gauge, filtration system Slurry Valve air pressure regulator/timer, elapsed time meter, and safety door interlocks.

Dawson-Macdonald Co.

845 Woburn Street, Wilmington, MA 01887

Tel: 1-800-556-4456 / Fax: (978) 657-8740

E-mail: info@dawson-macdonald.com

Website: www.dawson-macdonald.com

