

# BP-10

## *Shot Blasting Machine*



### SPECIFICATIONS

Production Capacity:	+up to 1,500 ft <sup>2</sup> /hr
Blast Pattern Width:	10"
Travel Speed:	0-100 ft/min
Blast Motor:	10 hp
Voltage:	460v, 3-phase, 60 hz
Amperage:	11.8 A
Weight:	730 lbs
Dimensions (LxWxH):	63" x 17" x 40"
Power Cord:	55 ft.

### FEATURES AND BENEFITS

- Finger tip speed and reverse control
- Easily accessible panel controls
- High-torque DC ground drive
- High speed, heavy duty bearing unit
- Precision manufactured liner package

The BP-10 is designed for medium-to-large jobs including industrial plant and warehouse floors, parking garages, and bridge or ship decks. The BP-10 is an electric, self-propelled machine with a 10" blast pattern. The BP-10 operates on 460 V, 3-phase power. The BP-10 is based on a tried and true design, offering robust construction and industry leading productivity. When coupled with the BP-5-54 dust collector, the BP-10 is a spectacular option for your surface preparation fleet without sacrificing quality, durability, and operator comfort.



**BP-5-54**

**Recommended dust collector**  
(see separate data sheet for specifications)



+Production rates will vary between material being removed and from job-to-job. This production rate represents production values under ideal conditions.



**Dawson-Macdonald Co., Inc.**  
845 Woburn Street - Wilmington, MA 01887  
Tel: (800) 556-4456 (toll free) / Fax: (978) 657-8740  
E-mail: [info@dawson-macdonald.com](mailto:info@dawson-macdonald.com)  
Website: [www.dawson-macdonald.com](http://www.dawson-macdonald.com)

# BP-5-54

## *Dust Collector*



The BP-5-54 is designed to accompany the BP-10 on medium-to-large jobs including industrial plant and warehouse floors, parking garages, and bridge or ship decks. The BP-5-54 operates on 460 V, 3-phase power. The BP-5-54 is based on a tried and true design, offering robust construction and industry leading productivity. When coupled with the BP-10 shot blasting unit, the BP-5-54 is a spectacular option for your surface preparation fleet without sacrificing quality, durability, and operator comfort.

### SPECIFICATIONS

<b>Blower Motor:</b>	<b>5 hp</b>
<b>Voltage:</b>	<b>460v, 3-phase, 60 hz</b>
<b>Amperage:</b>	<b>5.8 A</b>
<b>Power Cord:</b>	<b>55 ft.</b>

### FEATURES AND BENEFITS

- **Standard HEPA filter**
- **Reverse pulse filter cleaning**
- **Locking swivel casters**
- **Heavy duty blower housing**
- **Blower motor quick disconnect to remove cover**



### BP-10

**Recommended shot blasting unit**  
(see separate data sheet for specifications)



+Production rates will vary between material being removed and from job-to-job. This production rate represents production values under ideal conditions.